BEST AVAILABLE COPY



WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

G06F 17/00

A2

(11) International Publication Number: WO 00/54168

(43) International Publication Date: 14 September 2000 (14.09.00)

GB

GB

(21) International Application Number: PCT/GB00/00718

(22) International Filing Date: 1 March 2000 (01.03.00)

(30) Priority Data:
9905201.1
5 March 1999 (05.03.99)
9905186.4
5 March 1999 (05.03.99)

9905160.9 5 March 1999 (05.03.99) GB 9905199.7 5 March 1999 (05.03.99) GB 9905187.2 5 March 1999 (05.03.99) GB

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 30-2 3-chome Shimomaruko, Ohta-Ku, Tokyo (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CHARLESWORTH, Jason, Peter, Andrew [GB/GB]; Canon Research Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YJ (GB). RAJAN, Jebu, Jacob [IE/GB]; Canon Research Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YJ (GB). GARNER, Philip, Neil [GB/GB]; Canon Research Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YT (GB).


(74) Agents: BERESFORD, Keith, Denis, Lewis et al.; Beresford & Co., 2-5 Warwick Court, High Holborn, London WCIR 5DJ (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: DATABASE ANNOTATION AND RETRIEVAL



(57) Abstract

A data structure is provided for annotating data files within a database. The annotation data comprises a phoneme and word lattice which allows the quick and efficient searching of data files within the database in response to a user's input query. The structure of the annotation data is such that it allows the input query to be made by voice and can be used for annotating various kinds of data files, such as audio data files, video data files, multimedia data files etc. The annotation data may be generated from the data files themselves or may be input by the user either from a voiced input or from a typed input.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		. 31	20				CT	Slovenia
	AL	Albania	ES	Spain	LS	Lesotho	SI	
	AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
	AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
	ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
	AZ	Azerbaijan	GB ·	United Kingdom	MC	Monaco	TD	Chad
	BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
	BB	Barbados -	GH	Ghana	MG	Madagascar	TJ	Tajikistan
	BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
	BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
	BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
	BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
	BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
	BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
	CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
	CF	Central African Republic	JР	Japan	NE	Niger	٧N	Viet Nam
ı	CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
	CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
	CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
ı	CM	Cameroon		Republic of Korea	PL	Poland		
	CN	China	KR	Republic of Korea	PT	Portugal		
	CU	Cuba	KZ	Kazakstan	RO	Romania		
i	CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
1	DE	Germany	LI	Liechtenstein	SD	Sudan		
l	DK	Denmark	LK	Sri Lanka	SE	Sweden		
i	EE	Estonia	LR	Liberia	SG	Singapore		

DATABASE ANNOTATION AND RETRIEVAL

The present invention relates to the annotation of data files which are to be stored in a database for facilitating their subsequent retrieval. The present invention is also concerned with a system for generating the annotation data which is added to the data file and to a system for searching the annotation data in the database to retrieve a desired data file in response to a user's input query.

Databases of information are well known and suffer from the problem of how to locate and retrieve the desired information from the database quickly and efficiently. Existing database search tools allow the user to search the database using typed keywords. Whilst this is quick and efficient, this type of searching is not suitable for various kinds of databases, such as video or audio

20

25

databases.

5

10

15

According to one aspect, the present invention aims to provide a data structure which will allow the annotation of data files within a database which will allow a quick and efficient search to be carried out in response to a user's input query.

According to one aspect, the present invention provides data defining a phoneme and word lattice for use as an annotation data for annotating data files to be stored within a database. Preferably, the data defines a plurality of nodes within the lattice and a plurality of links connecting the nodes within the lattice and further data associates a plurality of phonemes with a respective plurality of links and further data associates at least one word with at least one of said links.

10

According to another aspect, the present invention provides a method of searching a database comprising the annotation data discussed above, in response to an input query by a user. The method preferably comprises the generating phoneme data and corresponding to the user's input query; searching the database using the word data corresponding to the user's query; selecting a portion of the data defining the phoneme and word lattice in the database for further searching in response to the results of the word search; searching said selected portion of the database using said phoneme data corresponding to the user's input query; and outputting the search results.

- 15 According to this aspect, the present invention also provides an apparatus for searching a database which employs the annotation data discussed above for annotating data files therein. The apparatus preferably comprises means for generating phoneme data and word data 20 corresponding to a user's input query; means searching the database using the word data corresponding to the user's input query to identify similar words within the database; means for selecting a portion of the annotation data in the database for further searching in 25 response to the results of the word search; means for searching the selected portion using the phoneme data corresponding to the user's input query; and means for outputting the search results.
- The phoneme and annotation data for a data file may be generated from the data file itself or from a typed or spoken annotation input by the user.
- Exemplary embodiments of the present invention will now be described with reference to the accompanying figures,

in which:

Figure 1 is a schematic view of a computer which is programmed to operate an embodiment of the present invention;

Figure 2 is a block diagram showing a phoneme and word annotator unit which is operable to generate phoneme and word annotation data for appendage to a data file;

10

20

25

pushage was a successive to

5

Figure 3 is a block diagram illustrating one way in which the phoneme and word annotator can generate the annotation data from an input video data file;

15 Figure 4a is a schematic diagram of a phoneme lattice for an example audio string from the input video data file;

Figure 4b is a schematic diagram of a word and phoneme lattice embodying one aspect of the present invention, for an example audio string from the input video data file:

Figure 5 is a schematic block diagram of a user's terminal which allows the user to retrieve information from the database by a voice query;

Figure 6a is a flow diagram illustrating part of the flow control of the user terminal shown in Figure 5;

Figure 6b is a flow diagram illustrating the remaining part of the flow control of the user terminal shown in Figure 5;

Figure 7 is a flow diagram illustrating the way in which a search engine forming part of the user's terminal

carries out a phoneme search within the database;

Figure 8 is a schematic diagram illustrating the form of a phoneme string and four M-GRAMS generated from the phoneme string;

Figure 9 is a plot showing two vectors and the angle between the two vectors;

- 10 Figure 10 is a schematic diagram of a pair of word and phoneme lattices, for example audio strings from two speakers;
- Figure 11 is a schematic block diagram illustrating a user terminal which allows the annotation of a data file with annotation data generated from an audio signal input from a user;
- Figure 12 is a schematic diagram of phoneme and word
 lattice annotation data which is generated for an example
 utterance input by the user for annotating a data file;

Figure 13 is a schematic block diagram illustrating a user terminal which allows the annotation of a data file with annotation data generated from a typed input from a user;

Figure 14 is a schematic diagram of phoneme and word lattice annotation data which is generated for a typed input by the user for annotating a data file;

Figure 15 is a block schematic diagram showing the form of a document annotation system;

35 Figure 16 is a block schematic diagram of an alternative

30

document annotation system;

Figure 17 is a block schematic diagram of another document annotation system;

5

Figure 18 is a schematic block diagram illustrating a user terminal which is operable to access a database located on a remote server via a data network in response to an input utterance by the user;

10

Figure 19 is a schematic block diagram of a user terminal which allows a user to access a database located in a remote server in response to an input utterance from the user;

15

Figure 20 is a schematic block diagram of a user terminal which allows a user to access a database by a typed input query; and

20

Figure 21 is a schematic block diagram illustrating the way in which a phoneme and word lattice can be generated from script data contained within a video data file.

25

using dedicated hardware circuits, but the embodiment to be described is implemented in computer software or code, which is run in conjunction with processing hardware such as a personal computer, work station, photocopier, facsimile machine, personal digital assistant (PDA) or

Embodiments of the present invention can be implemented

30 the like.

Figure 1 shows a personal computer (PC) 1 which is programmed to operate an embodiment of the present invention. A keyboard 3, a pointing device 5, a microphone 7 and a telephone line 9 are connected to the

35

PC 1 via an interface 11. The keyboard 3 and pointing device 5 enable the system to be controlled by a user. The microphone 7 converts acoustic speech signals from the user into equivalent electrical signals and supplies them to the PC 1 for processing. An internal modem and speech receiving circuit (not shown) is connected to the telephone line 9 so that the PC 1 can communicate with, for example, a remote computer or with a remote user.

10. The programme instructions which make the PC 1 operate in accordance with the present invention may be supplied for use with an existing PC 1 on, for example, a storage device such as a magnetic disc 13, or by downloading the software from the Internet (not shown) via the internal modem and telephone line 9.

DATA FILE ANNOTATION

Figure 2 is a block diagram illustrating the way in which annotation data 21 for an input data file 23 is generated 20 in this embodiment by a phoneme and word annotating unit. As shown, the generated phoneme and word annotation data 21 is then combined with the data file 23 in the data combination unit 27 and the combined data file output thereby is input to the database 29. 25 embodiment, the annotation data 21 comprises a combined phoneme (or phoneme like) and word lattice which allows the user to retrieve information from the database by a query. As those skilled in the art will appreciate, the data file 23 can be any kind of data 30 file, such as, a video file, an audio file, a multimedia file etc.

A system has been proposed to generate N-Best word lists for an audio stream as annotation data by passing the 35 audio data from a video data file through an automatic

9

As shown in Figure 3, in this embodiment, the audio data 31-2 is input to an automatic speech recognition unit 33, operable to generate a phoneme corresponding to the stream of audio data 31-2. Such an automatic speech recognition unit 33 is commonly available in the art and will not be described in further detail. The reader is referred to, for example, the book entitled 'Fundamentals of Speech Recognition' by Lawrence Rabiner and Biing-Hwang Juang and, in particular, to pages 42 to 50 thereof, for further information on this type of speech recognition system.

5

10

Figure 4a illustrates the form of the phoneme lattice data output by the speech recognition unit 33, for the input audio corresponding to the phrase '...tell me about 15 Jason...'. As shown, the automatic speech recognition unit 33 identifies a number of different possible phoneme strings which correspond to this input audio utterance. For example, the speech recognition system considers that the first phoneme in the audio string is either a /t/ or 20 a /d/. As is well known in the art of speech recognition, these different possibilities can have their weighting which is generated by recognition unit 33 and is indicative of the confidence of the speech recognition unit's output. For example, 25 the phoneme /t/ may be given a weighting of 0.9 and the phoneme /d/ may be given a weighting of 0.1, indicating that the speech recognition system is fairly confident that the corresponding portion of audio represents the phoneme /t/, but that it still may be the phoneme /d/. 30 In this embodiment, however, this weighting of the phonemes is not performed.

As shown in Figure 3, the phoneme lattice data 35 output by the automatic speech recognition unit 33 is input to

a word decoder 37 which is operable to identify possible words within the phoneme lattice data 35. embodiment, the words identified by the word decoder 37 are incorporated into the phoneme lattice data structure. 5 For example, for the phoneme lattice shown in Figure 4a, the word decoder 37 identifies the words 'tell', 'dell', 'term', 'me', 'a', 'boat', 'about', 'chase' and 'sun'. As shown in Figure 4b, these identified words are added to the phoneme lattice data structure output by the 10 speech recognition unit 33, to generate a phoneme and word lattice data structure which forms the annotation data 31-3. This annotation data 31-3 is then combined with the video data file 31 to generate an augmented video data file 31' which is then stored in the database As those skilled in the art will appreciate, in a 15 similar way to the way in which the audio data 31-2 is synchronised with the video data 31-1, annotation data 31-3 is also time synchronised and associated with the corresponding video data 31-1 and 20 audio data 31-2, so that a desired portion of the video and audio data can be retrieved by searching for and locating the corresponding portion of the annotation data 31-3.

In this embodiment, the annotation data 31-3 stored in the database 29 has the following general form:

time of start

HEADER

- flag if word if phoneme if mixed
- time index associating the location of blocks of annotation data within memory to a given time point.
 - word set used (i.e. the dictionary)
 - phoneme set used
- the language to which the vocabulary

10

15

25

30

11

pertains

Block(i) i = 0,1,2,...node N_1 j = 0,1,2,...

- time offset of node from start of block
- phoneme links (k) k = 0,1,2....
 offset to node N_j = N_k-N_j (N_k is node to
 which link K extends) or if N_k is in
 block (i+1) offset to node N_j = N_k+N_b-N_j
 (where N_b is the number of nodes in
 block (i))

phoneme associated with link (k)

- word links (1) $l = 0, 1, 2, \ldots$ offset to node $N_j = N_i - N_j$ (N_j is node to which link l extends) or if N_k is in block (i+1) offset to node $N_j = N_k + N_b - N_j$ (where N_b is the number of nodes in block (i)) word associated with link (1)

The time of start data in the header can identify the time and date of transmission of the data. For example, if the video file is a news broadcast, then the time of start may include the exact time of the broadcast and the date on which it was broadcast.

The flag identifying if the annotation data is word annotation data, phoneme annotation data or if it is mixed is provided since not all the data files within the database will include the combined phoneme and word lattice annotation data discussed above, and in this case, a different search strategy would be used to search this annotation data.

In this embodiment, the annotation data is divided into blocks in order to allow the search to jump into the

12

middle of the annotation data for a given audio data stream. The header therefore includes a time index which associates the location of the blocks of annotation data within the memory to a given time offset between the time of start and the time corresponding to the beginning of the block.

The header also includes data defining the word set used (i.e. the dictionary), the phoneme set used and the language to which the vocabulary pertains. The header may also include details of the automatic speech recognition system used to generate the annotation data and any appropriate settings thereof which were used during the generation of the annotation data.

15

20

25

10

5

The blocks of annotation data then follow the header and identify, for each node in the block, the time offset of the node from the start of the block, the phoneme links which connect that node to other nodes by phonemes and word links which connect that node to other nodes by words. Each phoneme link and word link identifies the phoneme or word which is associated with the link. They also identify the offset to the current node. For example, if node N_{50} is linked to node N_{55} by a phoneme link, then the offset to node N_{50} is 5. As those skilled in the art will appreciate, using an offset indication like this allows the division of the continuous annotation data into separate blocks.

In an embodiment where an automatic speech recognition unit outputs weightings indicative of the confidence of the speech recognition units output, these weightings or confidence scores would also be included within the data structure. In particular, a confidence score would be provided for each node which is indicative of the

13

confidence of arriving at the node and each of the phoneme and word links would include a transition score depending upon the weighting given to the corresponding phoneme or word. These weightings would then be used to control the search and retrieval of the data files by discarding those matches which have a low confidence score.

DATA FILE RETRIEVAL

5

Figure 5 is a block diagram illustrating the form of a 10 user terminal 59 which can be used to retrieve the annotated data files from the database 29. terminal 59 may be, for example, a personal computer, hand held device or the like. As shown, embodiment, the user terminal 59 comprises the database 15 annotated data files, automatic 29 of an recognition unit 51, a search engine 53, a control unit 55 and a display 57. In operation, the automatic speech recognition unit 51 is operable to process an input voice 20 query from the user 39 received via the microphone 7 and the input line 61 and to generate therefrom corresponding phoneme and word data. This data may also take the form of a phoneme and word lattice, but this is not essential. This phoneme and word data is then input to the control 25 unit 55 which is operable to initiate an appropriate search of the database 29 using the search engine 53. The results of the search, generated by the search engine 53, are then transmitted back to the control unit 55 which analyses the search results and generates and 30 displays appropriate display data to the user via the display 57.

Figures 6a and 6b are flow diagrams which illustrate the way in which the user terminal 59 operates in this embodiment. In step s1, the user terminal 59 is in an

14

idle state and awaits an input query from the user 39. Upon receipt of an input query, the phoneme and word data for the input query is generated in step s3 by the automatic speech recognition unit 51. The control unit 55 then instructs the search engine 53, in step s5, to perform a search in the database 29 using the word data generated for the input query. The word search employed in this embodiment is the same as is currently being used in the art for typed keyword searches, and will not be described in more detail here. If in step s7, the control unit 55 identifies from the search results, that a match for the user's input query has been found, then it outputs the search results to the user via the display 57.

15

20

25

30

35

10

5

In this embodiment, the user terminal 59 then allows the user to consider the search results and awaits the user's confirmation as to whether or not the results correspond to the information the user requires. If they are, then the processing proceeds from step sll to the end of the processing and the user terminal 59 returns to its idle state and awaits the next input query. If, however, the user indicates (by, for example, inputting an appropriate voice command) that the search results do not correspond to the desired information, then the processing proceeds from step sll to step sl3, where the search engine 53 performs a phoneme search of the database 29. in this embodiment, the phoneme search performed in step sl3 is not of the whole database 29, since this could take several hours depending on the size of the database 29.

Instead, the phoneme search performed in step s13 uses the results of the word search performed in step s5 to identify one or more portions within the database which

15

may correspond to the user's input query. The way in which the phoneme search performed in step s13 is performed in this embodiment, will be described in more phoneme search has the later. After detail performed, the control unit 55 identifies, in step s15, If a match has been found, if a match has been found. then the processing proceeds to step s17 where the control unit 55 causes the search results to be displayed to the user on the display 57. Again, the system then awaits the user's confirmation as to whether or not the search results correspond to the desired information. If the results are correct, then the processing passes from step s19 to the end and the user terminal 59 returns to its idle state and awaits the next input query. however, the user indicates that the search results do not correspond to the desired information, then the processing proceeds from step s19 to step s21, where the control unit 55 is operable to ask the user, via the display 57, whether or not a phoneme search should be performed of the whole database 29. If in response to this query, the user indicates that such a search should be performed, then the processing proceeds to step s23 where the search engine performs a phoneme search of the entire database 29.

25

30

35

5

10

15

20

On completion of this search, the control unit 55 identifies, in step s25, whether or not a match for the user's input query has been found. If a match is found, then the processing proceeds to step s27 where the control unit 55 causes the search results to be displayed to the user on the display 57. If the search results are correct, then the processing proceeds from step s29 to the end of the processing and the user terminal 59 returns to its idle state and awaits the next input query. If, on the other hand, the user indicates that the

16

search results still do not correspond to the desired information, then the processing passes to step s31 where the control unit 55 queries the user, via the display 57, whether or not the user wishes to redefine or amend the search query. If the user does wish to redefine or amend the search query, then the processing returns to step s3 where the user's subsequent input query is processed in a similar manner. If the search is not to be redefined or amended, then the search results and the user's initial input query are discarded and the user terminal 59 returns to its idle state and awaits the next input query.

PHONEME SEARCH

5

10

30

35

15 As mentioned above, in steps s13 and s23, the search engine 53 compares the phoneme data of the input query with the phoneme data in the phoneme and word lattice annotation data stored in the database 29. techniques can be used including standard pattern 20 matching techniques such as dynamic programming, to carry out this comparison. In this embodiment, a technique which we refer to as M-GRAMS is used. This technique was proposed by Ng, K. and Zue, V.W. and is discussed in, for example, the paper entitled "Subword unit representations 25 spoken document retrieval" published the proceedings of Eurospeech 1997.

The problem with searching for individual phonemes is that there will be many occurrences of each phoneme within the database. Therefore, an individual phoneme on its own does not provide enough discriminability to be able to match the phoneme string of the input query with the phoneme strings within the database. Syllable sized units, however, are likely to provide more discriminability, although they are not easy to identify.

15

20

The M-GRAM technique presents a suitable compromise between these two possibilities and takes overlapping fixed size fragments, or M-GRAMS, of the phoneme string to provide a set of features. This is illustrated in Figure 8, which shows part of an input phoneme string having phonemes a, b, c, d, e, and f, which are split into four M-GRAMS (a, b, c), (b, c, d), (c, d, e) and (d, e, f). In this illustration, each of the four M-GRAMS comprises a sequence of three phonemes which is unique and represents a unique feature (f_i) which can be found within the input phoneme string.

Therefore, referring to Figure 7, the first step s51 in performing the phoneme search in step s13 shown in Figure 6, is to identify all the different M-GRAMS which are in the input phoneme data and their frequency of occurrence. Then, in step s53, the search engine 53 determines the frequency of occurrence of the identified M-GRAMS in the selected portion of the database (identified from the word search performed in step s5 in Figure 6). To illustrate this, for a given portion of the database and for the example M-GRAMS illustrated in Figure 8, this yields the following table of information:

25	M-GRAM (feature (f _i))	Input phoneme string frequency of occurrence (g)	Phoneme string of selected portion of database (<u>a</u>)	
-	M ₁	1	0	
	M ₂	2	2	
	M ₃	3	2	
30	M ₄	1	1	

10

15

20

the way of the same to be

Next, in step s55, the search engine 53 calculates a similarity score representing a similarity between the phoneme string of the input query and the phoneme string of the selected portion from the database. embodiment, this similarity score is determined using a cosine measure using the frequencies of occurrence of the identified M-GRAMS in the input query and in the selected portion of the database as vectors. The philosophy behind this technique is that if the input phoneme string is similar to the selected portion of the database phoneme string, then the frequency of occurrence of the M-GRAM features will be similar for the two phoneme strings. Therefore, if the frequencies of occurrence of M-GRAMS are considered to be vectors considering the second and third columns in the above table as vectors), then if there is a similarity between the input phoneme string and the selected portion of the database, then the angle between these vectors should be This is illustrated in Figure 9 for twodimensional vectors a and q, with the angle between the vectors given as θ . In the example shown in Figure 8, the vectors $\underline{\mathbf{a}}$ and $\underline{\mathbf{q}}$ will be four dimensional vectors and the similarity score can be calculated from:

$$SCORE = COS \ \theta = \frac{\underline{a} \cdot \underline{q}}{|\underline{a}| |\underline{q}|}$$
 (1)

25 This score is then associated with the current selected portion of the database and stored until the end of the search. In some applications, the vectors used in the calculation of the cosine measure will be the logarithm of these frequencies of occurrences, rather than the frequencies of occurrences themselves.

19

The processing then proceeds to step s57 where the search engine 53 identifies whether or not there are any more selected portions of phoneme strings from the database 29. If there are, then the processing returns to step s53 where a similar procedure is followed to identify the score for this portion of the database. If there are no more selected portions, then the searching ends and the processing returns to step s15 shown in Figure 6, where the control unit considers the scores generated by the search engine 53 and identifies whether or not there is a match by, for example, comparing the calculated scores with a predetermined threshold value.

As those skilled in the art will appreciate, a similar matching operation will be performed in step s23 shown in Figure 6. However, since the entire database is being searched, this search is carried out by searching each of the blocks discussed above in turn.

20 ALTERNATIVE EMBODIMENTS

5

10

15

25

30

35

As those skilled in the art will appreciate, this type of phonetic and word annotation of data files in a database provides a convenient and powerful way to allow a user to search the database by voice. In the illustrated embodiment, a single audio data stream was annotated and stored in the database for subsequent retrieval by the user. As those skilled in the art will appreciate, when the input data file corresponds to a video data file, the audio data within the data file will usually include audio data for different speakers. Instead of generating a single stream of annotation data for the audio data, separate phoneme and word lattice annotation data can be generated for the audio data of each speaker. This may be achieved by identifying, from the pitch or from another distinguishing feature of the speech signals, the

10

15

20

25

30

35

audio data which corresponds to each of the speakers and then by annotating the different speaker's audio separately. This may also be achieved if the audio data was recorded in stereo or if an array of microphones were used in generating the audio data, since it is then possible to process the audio data to extract the data for each speaker.

Figure 10 illustrates the form of the annotation data in such an embodiment, where a first speaker utters the words "... this so" and the second speaker replies "yes". As illustrated, the annotation data for the different speakers' audio data are time synchronised, relative to each other, so that the annotation data is still time synchronised to the video and audio data within the data file. In such an embodiment, the header information in the data structure should preferably include a list of the different speakers within the annotation data and, for each speaker, data defining that speaker's language, accent, dialect and phonetic set, and each block should identify those speakers that are active in the block.

In the above embodiments, a speech recognition system was used to generate the annotation data for annotating a data file in the database. As those skilled in the art will appreciate, other techniques can be used to generate this annotation data. For example, a human operator can listen to the audio data and generate a phonetic and word transcription to thereby manually generate the annotation data.

In the above embodiments, the annotation data was generated from audio stored in the data file itself. As those skilled in the art will appreciate, other techniques can be used to input the annotation data.

21

Figure 11 illustrates the form of a user terminal 59 which allows a user to input voice annotation data via the microphone 7 for annotating a data file 91 which is to be stored in the database 29. In this embodiment, the data file 91 comprises a two dimensional image generated by, for example, a camera. The user terminal 59 allows the user 39 to annotate the 2D image with an appropriate annotation which can be used subsequently for retrieving the 2D image from the database 29. In this embodiment, the input voice annotation signal is converted, by the automatic speech recognition unit 51, into phoneme and word lattice annotation data which is passed to the control unit 55. In response to the user's input, the control unit 55 retrieves the appropriate 2D file from the database 29 and appends the phoneme and word annotation data to the data file 91. The augmented data file is then returned to the database 29. During this annotating step, the control unit 55 is operable to display the 2D image on the display 57 so that the user can ensure that the annotation data is associated with the correct data file 91.

5

10

15

20

25

30

35

The automatic speech recognition unit 51 generates the phoneme and word lattice annotation data generating a phoneme lattice for the input utterance; (ii) then identifying words within the phoneme lattice; and (iii) finally by combining the two. Figure 12 illustrates the form of the phoneme and word lattice annotation data generated for the input utterance "picture of the Taj-Mahal". As shown, the automatic speech recognition unit identifies a number of different possible phoneme strings which correspond to this input utterance. As shown in Figure 12, the words which the automatic speech recognition unit 51 identifies within the phoneme lattice are incorporated into the phoneme

WO 00/54168

lattice data structure. As shown, for the example phrase, the automatic speech recognition unit 51 identifies the words "picture", "of", "off", "the", "other", "ta", "tar", "jam", "ah", "hal", "ha" and "al". The control unit 55 is then operable to add this annotation data to the 2D image data file 91 which is then stored in a database 29.

As those skilled in the art will appreciate, this embodiment can be used to annotate any kind of image such as x-rays of patients, 3D videos of, for example, NMR scans, ultrasound scans etc. It can also be used to annotate one-dimensional data, such as audio data or seismic data.

15

20

25

30

35

5

In the above embodiment, a data file was annotated from a voiced annotation. As those skilled in the art will appreciate, other techniques can be used to input the annotation. For example, Figure 13 illustrates the form of a user terminal 59 which allows a user to input typed annotation data via the keyboard 3 for annotating a data file 91 which is to be stored in a database 29. embodiment, the typed input is converted, by the phonetic transcription unit 75, into the phoneme and word lattice annotation data (using an internal phonetic dictionary (not shown)) which is passed to the control unit 55. response to the user's input, the control unit 55 retrieves the appropriate 2D file from the database 29 and appends the phoneme and word annotation data to the data file 91. The augmented data file is then returned to the database 29. During this annotating step, the control unit 55 is operable to display the 2D image on the display 57 so that the user can ensure that the annotation data is associated with the correct data file 91.

23

Figure 14 illustrates the form of the phoneme and word lattice annotation data generated for the input utterance "picture of the Taj-Mahal". As shown in Figure 2, the phoneme and word lattice is an acyclic directed graph with a single entry point and a single exit point. It represents different parses of the user's input. As shown, the phonetic transcription unit 75 identifies a number of different possible phoneme strings which correspond to the typed input.

10

15

20

25

30

35

5

Figure 15 is a block diagram illustrating a document annotation system. In particular, as shown in Figure 15, a text document 101 is converted into an image data file by a document scanner 103. The image data file is then passed to an optical character recognition (OCR) unit 105 which converts the image data of the document 101 into This electronic text is then supplied electronic text. to a phonetic transcription unit 107 which is operable to generate phoneme and word annotation data 109 which is then appended to the image data output by the scanner 103 to form a data file 111. As shown, the data file 111 is then stored in the database 29 for subsequent retrieval. In this embodiment, the annotation data 109 comprises the combined phoneme and word lattice described above which allows the user to subsequently retrieve the data file 111 from the database 29 by a voice query.

Figure 16 illustrates a modification to the document annotation system shown in Figure 15. The difference between the system shown in Figure 16 and the system shown in Figure 15 is that the output of the optical character recognition unit 105 is used to generate the data file 113, rather than the image data output by the scanner 103. The rest of the system shown in Figure 16 is the same as that shown in Figure 15 and will not be

24

described further.

Figure 17 shows a further modification to the document annotation system shown in Figure 15. In the embodiment shown in Figure 17, the input document is received by a facsimile unit 115 rather than a scanner 103. The image data output by the facsimile unit is then processed in the same manner as the image data output by the scanner 103 shown in Figure 15, and will not be described again.

10

15

20

25

30

35

5

In the above embodiment, a phonetic transcription unit 107 was used for generating the annotation data for annotating the image or text data. As those skilled in the art will appreciate, other techniques can be used. For example, a human operator can manually generate this annotation data from the image of the document itself.

In the above embodiment, the database 29 automatic speech recognition unit were both located within the user terminal 59. As those skilled in the art will appreciate, this is not essential. Figure 18 illustrates an embodiment in which the database 29 and the search engine 53 are located in a remote server 60 and in which the user terminal 59 accesses and controls data files in the database 29 via the network interface units 67 and 69 and a data network 68 (such as the Internet). In operation, the user inputs a voice query via the microphone 7 which is converted into phoneme and word data by the automatic speech recognition unit 51. This data is then passed to the control unit which controls the transmission of this phoneme and word data over the data network 68 to the search engine 53 located within the remote server 60. The search engine 53 then carries out the search in accordance with the received phoneme and word data or controls the manipulation of the

10

BNESSON, Street Post 416519 1 -

data files (for example to control the playing, forwarding or rewinding of a video file) in accordance with the received phoneme and word data. The data retrieved from the database 29 or other data relating to the search is then transmitted back, via the data network 68, to the control unit 55 which controls the display of appropriate data on the display 57 for viewing by the user 39. In this way it is possible to retrieve and control data files in the remote server 60 without using significant computer resources in the server (since it is the user terminal 59 which converts the input speech into the phoneme and word data).

In addition to locating the database 29 and the search engine 53 in the remote server 60, it is also possible to 15 locate the automatic speech recognition unit 51 in the remote server 60. Such an embodiment is shown in Figure As shown in this embodiment, the input voice query from the user is passed via input line 61 to a speech 20 encoding unit 73 which is operable to encode the speech for efficient transfer through the data network 68. encoded data is then passed to the control unit 55 which transmits the data over the network 68 to the remote server 60, where it is processed by the automatic speech 25 recognition unit 51. The phoneme and word data generated by the speech recognition unit 51 for the input query is then passed to the search engine 53 for use in searching controlling data files in the database Appropriate data retrieved by the search engine 53 is 30 then passed, via the network interface 69 and the network 68, back to the user terminal 59. This data received back from the remote server is passed via the network interface unit 67 to the control unit 55 which generates and displays appropriate data on the display 57 for 35 viewing by the user.

15

20

25

30

35

In the above embodiments, the user inputs his query by Figure 20 shows an alternative embodiment in which the user inputs the query via the keyboard 3. shown, the text input via the keyboard 3 is passed to phonetic transcription unit 75 which is operable to generate a corresponding phoneme string from the input text. This phoneme string together with the words input via the keyboard 3 are then passed to the control unit 55 which initiates a search of database using the search engine 53. The way in which this search is carried out is the same as in the first embodiment and will not, therefore, be described again. As with the other embodiments discussed above, the phonetic transcription unit 75, search engine 53 and/or the database 29 may all be located in a remote server.

In the first embodiment, the audio data from the data 31 was passed through an automatic speech recognition unit in order the generate the phoneme annotation data. In some situations, a transcript of the audio data will be present in the data file. embodiment is illustrated in Figure 21. In this embodiment, the data file 81 represents a digital video file having video data 81-1, audio data 81-2 and script data 81-3 which defines the lines for the various actors in the video film. As shown, the script data 81-3 is passed through a text to phoneme converter 83, which generates phoneme lattice data 85 using a stored dictionary which translates words into possible sequences of phonemes. This phoneme lattice data 85 is then combined with the script data 81-3 to generate the above described phoneme and word lattice annotation data 81-4. This annotation data is then added to the data file 81 to generate an augmented data file 81' which is then added to the database 29. As those skilled in the art will WO 00/54168

appreciate, this embodiment facilitates the generation of separate phoneme and word lattice annotation data for the different speakers within the video data file, since the script data usually contains indications of who is talking. The synchronisation of the phoneme and word lattice annotation data with the video and audio data can then be achieved by performing a forced time alignment of the script data with the audio data using an automatic speech recognition system (not shown).

10

15

5

In the above embodiments, a phoneme (or phoneme-like) and word lattice was used to annotate a data file. As those skilled in the art of speech recognition and speech processing will realise, the word "phoneme" in the description and claims is not limited to its linguistic meaning but includes the various sub-word units that are identified and used in standard speech recognition systems.

CLAIMS:

5

10

15

1. Data defining a phoneme and word lattice, the data comprising:

data for defining a plurality of nodes within the lattice and a plurality of links connecting the nodes within the lattice;

data associating a plurality of phonemes with a respective plurality of links; and

data associating at least one word with at least one of said links.

- 2. Data according to any preceding claim, wherein said data defining said phoneme and word lattice is arranged in blocks of nodes.
- 3. Data according to claim 1, further comprising data defining time stamp information for each of said nodes.
- 20 4. Data according to claim 3, arranged in blocks of equal time duration.
 - 5. Data according to claim 2 or 4, further comprising data defining each blocks location within said database.
 - Data according to claim 3 or any claim dependent thereon, wherein said data defining a phoneme and word lattice is associated with further data defining a time sequential signal, and wherein said time information is time synchronised with said time sequential signal.
 - 7. Data according to claim 6, wherein said further data defines an audio and/or video signal.

30

25

8. Data according to claim 7, wherein said further data defines at least speech data and wherein said data defining said phoneme and word lattice is derived from said further data.

5

9. Data according to claim 8, wherein said speech data comprises audio data and wherein said data defining said phoneme and word lattice is derived by passing said audio signal through an automatic speech recognition system.

10

10. Data according to claim 8 or 9, wherein said speech data defines the parol of a plurality of speakers, and wherein said data defines a separate phoneme and word lattice for the parol of each speaker.

¹ 15

11. Data according to any preceding claim, further comprising data defining a weighting for the phonemes and/or words associated with said links.

20

12. Data according to any preceding claim, wherein at least one of said nodes is connected to a plurality of other nodes by a plurality of links.

25

13. Data according to claim 12, wherein at least one of said plurality of links connecting said node to said plurality of other nodes is associated with a phoneme and wherein at least one of said links connecting said node to said plurality of other nodes is associated with a word.

30

35

- 14. A method of searching a database comprising data according to any preceding claim, in response to an input query, the method comprising the steps of:
- generating phoneme data and/or word data corresponding to the input query;

10

15

searching the phoneme and word lattice using the phoneme and/or word data generated for the input query; and

outputting search results in dependence upon the results of said searching step.

- 15. A method according to claim 14, wherein said searching step comprises the steps of:
- (i) searching the phoneme and word lattice using the word data generated for the user's input query to identify similar words within the phoneme and word lattice;
- (ii) selecting one or more portions of the phoneme and word lattice for further searching in response to the results of said word search; and
- (iii) searching said one or more selected portions of the phoneme and word lattice using the phoneme data generated for the user's input query.
- 20 16. A method according to claim 15, wherein the results of the word search are output to the user before the phoneme search is performed on the selected portions of the database.
- 17. A method according to claim 16, wherein said phoneme search is only performed in response to a further input by the user in response to the outputting of the results from the word search.
- 18. A method according to any of claims 15 to 17, wherein said phoneme search is carried out by identifying a number of features within the phoneme sequence corresponding to the user's input query and identifying similar features within the data defining said phoneme lattice within the database.

15

20

25

30

- 19. A method according to claim 18, wherein each of said features represents a unique sequence of phonemes within the phoneme data of the user's input query.
- 20. A method according to claim 19, wherein said phoneme search employs a cosine measure to indicate the similarity between the phoneme data corresponding to the user's input query and the phoneme data within the database.

21. A method according to any of claims 14 to 20, wherein said search results are output to a display.

- 22. A method according to any of claims 14 to 21, wherein said input query by the user is input by voice, and wherein said step of generating phoneme data and word data employs an automatic speech recognition system.
- 23. A method according to any of claims 14 to 21, wherein said input query is a typed input and wherein said step of generating phoneme data and word data employs a text-to-phoneme converter.
 - 24. An apparatus for searching a database comprising data according to any of claims 1 to 13, in response to an input query, the apparatus comprising:

means for generating phoneme data and/or word data corresponding to the input query;

means for searching the phoneme and word lattice using the phoneme and/or word data generated for the input query; and

means for outputting search results in dependence upon the output from said searching means.

35 25. An apparatus according to claim 24, wherein said

10

15

20

25

searching means comprises:

- (i) means for searching the phoneme and word lattice using the word data generated for the user's input query to identify similar words within the phoneme and word lattice;
- (ii) means for selecting one or more portions of the phoneme and word lattice for further searching in response to the results of said word search; and
- (iii) means for searching said one or more selected portions of the phoneme and word lattice using the phoneme data generated for the user's input query.
- 26. An apparatus according to claim 25, wherein said output means is operable to output the results of the word search to the user before the phoneme search is performed on the selected portions of the database.
- 27. An apparatus according to claim 26, wherein said phoneme search is only performed in response to a further input by the user in response to the outputting of the results from the word search.
- 28. An apparatus according to any of claims 25 to 27, wherein said phoneme search is carried out by identifying a number of features within the phoneme sequence corresponding to the user's input query and identifying similar features within the data defining said phoneme lattice within the database.
- 29. An apparatus according to claim 28, wherein each of said features represents a unique sequence of phonemes within the phoneme data of the user's input query.
- 30. An apparatus according to claim 29, wherein said phoneme search employs a cosine measure to indicate the

20

similarity between the phoneme data corresponding to the user's input query and the phoneme data within the database.

- 5 31. An apparatus according to any of claims 24 to 30, wherein said output means comprises a display.
- 32. An apparatus according to any of claims 24 to 31, wherein said input query by the user is a voice query, and wherein said means for generating phoneme data and word data comprises an automatic speech recognition system which is operable to generate said phoneme data and a word decoder which is operable to generate said word data.
 - 33. An apparatus according to any of claims 24 to 31, wherein said input query is a typed query and wherein said means for generating phoneme data and word data comprises a text-to-phoneme converter which is operable to generate said phoneme data.
 - 34. An apparatus for generating annotation data for use in annotating a data file comprising audio data, the apparatus comprising:
- 25 an automatic speech recognition system for generating phoneme data for audio data in the data file;
 - a word decoder for identifying possible words within the phoneme data generated by the automatic speech recognition system; and
- generating means for generating annotation data by combining the generated phoneme data and the decoded words.
- 35. An apparatus for generating annotation data for usein annotating a data file comprising text data, the

10

15

20

25

30

35

apparatus comprising:

a text to phoneme converter for generating phoneme data for text data in the data file; and

generating means for generating annotation data by combining the phoneme data and words in the text data.

36. An apparatus for generating annotation data for use in annotating a data file, the apparatus comprising:

input means for receiving an input voice signal; speech recognition means for converting the input voice signal into phoneme data and words; and

generating means for generating annotation data by combining the phoneme data and the words.

37. An apparatus for generating annotation data for use in annotating a data file, the apparatus comprising:

input means for receiving a typed input from a user; converting means for converting words in the typed input into phoneme data; and

generating means for generating annotation data by combining the phoneme data and words in the typed input.

38. An apparatus for generating annotation data for use in annotating a data file, the apparatus comprising:

means for receiving image data representative of text;

character recognition means for converting said image data into text data;

converting means for converting words in the text data into phoneme data; and

generating means for generating annotation data by combining the phoneme data and words in the text data.

39. An apparatus according to any of claims 34 to 38, wherein said annotation data defines a phoneme and word

10

、15

lattice and wherein said generating means comprises:

- (i) means for generating data defining a plurality of nodes within the lattice and a plurality of links connecting the nodes within the lattice;
- (ii) means for generating data associating a plurality of phonemes of the phoneme data with a respective plurality of links; and
- (iii) means for generating data associating at least one of the words with at least one of said links..
- 40. An apparatus according to claim 39, wherein said generating means is operable to generate said data defining said phoneme and word lattice in blocks of said nodes.
- 41. An apparatus according to claim 39 or 40, wherein said generating means is operable to generate data defining time stamp information for each of said nodes.
- 42. An apparatus according to claim 41, wherein said generating means is arranged to generate said phoneme and word lattice data in blocks of equal time duration.
- 43. An apparatus according to claim 40, 41 or 42, wherein said generating means is operable to generate data which defines each block's location within a database.
- 44. An apparatus according to claim 41 or any claim dependent thereon, wherein said data file includes a time sequential signal, and wherein said generating means is operable to generate time stamp data which is time synchronised with said time sequential signal.
- 35 45. An apparatus according to claim 44, wherein said

20

25

30

time sequential signal is an audio and/or video signal.

- 46. An apparatus according to claim 34 or any claim dependent thereon, wherein said audio data includes audio data which defines the parol of a plurality of speakers, and wherein said generating means is operable to generate data which defines separate phoneme and word annotation data for the parol of each speaker.
- 47. An apparatus according to claim 35 or any claim dependent thereon, wherein said text data defines the parol of a plurality of speakers, and wherein said generating means is operable to generate data defining separate phoneme and word annotation data for the parol of each speaker.
 - 48. An apparatus according to claim 34 or any claim dependent thereon, wherein said speech recognition system is operable to generate data defining a weighting for the phonemes in the phoneme data.
 - 49. An apparatus according to claim 34 or any claim dependent thereon, wherein said word decoder is operable to generate data defining a weighting for the words identified within said phoneme data.
 - 50. An apparatus according to claim 39 or any claim dependent thereon, wherein said means for generating data defining a plurality of nodes and a plurality of links is operable to define at least one node which is connected to a plurality of other nodes by a plurality of links.
- 51. An apparatus according to claim 50, wherein at least one of said plurality of links connecting said node to said plurality of other nodes is associated with a

20

phoneme and wherein at least one of said links connecting said node to said plurality of other nodes is associated with a word.

- 5 52. An apparatus according to claim 36 or any claim dependent thereon, wherein said speech recognition means is operable to generate data defining a weighting for the phonemes in the phoneme data.
- 53. An apparatus according to claim 52, wherein said speech recognition means is operable to generate data defining a weighting for the words within the word data.
- 54. An apparatus according to claim 36 or 37 or any claim dependent thereon, further comprising means for associating said annotation data with said data file.
 - 55. An apparatus according to claim 37 or any claim dependent thereon, wherein said converting means comprises an automatic phonetic transcription unit which generates said phoneme data from words within the typed input.
- 56. An apparatus according to claim 38 or any claim dependent thereon, wherein said converting means comprises an automatic phonetic transcription unit which generates said phoneme data from words within the text data output by said character recognition means.
- 57. An apparatus according to claim 38 or any claim dependent thereon, further comprising means for associating said annotation data with either said image data representative of said text or with said text data.
- 35 58. An apparatus according to claim 38 or any claim

5

10

20

25

30

35

dependent thereon, wherein said receiving means comprises a document scanner or a facsimile machine.

59. A method of generating annotation data for use in annotating a data file comprising audio data, the method comprising the steps of:

using an automatic speech recognition system to generate phoneme data for audio data in the data file;

using a word decoder to identify possible words within the phoneme data generated by the automatic speech recognition system; and

generating annotation data by combining the generated phoneme data and the decoded words.

15 60. A method of generating annotation data for use in annotating a data file comprising text data, the method comprising the steps of:

using a text to phoneme converter to generate phoneme data for text data in the data file; and

generating annotation data by combining the phoneme data and words in the text data.

61. A method of generating annotation data for use in annotating a data file, the method comprising the steps of:

receiving an input voice signal;

processing the input voice signal using a speech recognition system to generate phoneme data and word data for the input voice signal; and

generating annotation data by combining the phoneme data and the word data generated for the input voice signal.

62. A method of generating annotation data for use in annotating a data file, the method comprising the steps

WO 00/54168 PCT/GB00/00718

39

of:

5

10

` 15

20

25

receiving a typed input;

converting words in the typed input into phoneme data; and

generating annotation data by combining the phoneme data and words in the typed input.

63. A method of generating annotation data for use in annotating a data file, the method comprising the steps of:

receiving image data representative of text;

converting said image data into text data using a character recognition unit;

converting words in the text data into phoneme data; and

generating annotation data by combining the phoneme data and words within the text data.

- 64. A method according to any of claims 59 to 63, wherein said annotation data defines a phoneme and word lattice and wherein said generating step comprises the steps of:
- (i) generating data defining a plurality of nodes within the lattice and a plurality of links connecting the nodes within the lattice;
- (ii) generating data associating a plurality of phonemes of the phoneme data with a respective plurality of links; and
- (iii) generating data associating at least one of the words with at least one of said links.
- 65. A method according to claim 64, wherein said generating step generates said data defining said phoneme and word lattice in blocks of said nodes.

- 66. A method according to claim 64 or 65, wherein said generating step generates data defining time stamp information for each of said nodes.
- 5 67. A method according to claim 66, wherein said generating step generates said phoneme and word lattice data in blocks of equal time duration.
- 68. A method according to claim 65, 66 or 67, wherein said generating step generates data which defines each block's location within a database.

15

- 69. A method according to claim 66 or any claim dependent thereon, wherein said data file includes a time sequential signal, and wherein said generating step generates time stamp data which is time synchronised with said time sequential signal.
- 70. A method according to claim 69, wherein said time sequential signal is an audio and/or video signal.
 - 71. A method according to claim 59 or any claim dependent thereon, wherein said audio data includes audio data which defines the parol of a plurality of speakers, and wherein said generating step generates data which defines separate phoneme and word annotation data for the parol of each speaker.
- 72. A method according to claim 60 or any claim dependent thereon, wherein said text data defines the parol of a plurality of speakers, and wherein said generating step generates data defining separate phoneme and word annotation data for the parol of each speaker.
- 35 73. A method according to claim 59 or any claim

: 15

20

25

30

35

dependent thereon, wherein said speech recognition system generates data defining a weighting for the phonemes associated with said links.

- 5 74. A method according to claim 59 or any claim dependent thereon, wherein said word decoder generates data defining a weighting for the words associated with said links.
- 75. A method according to claim 64 or any claim dependent thereon, wherein said step of defining a plurality of nodes and a plurality of links defines at least one node which is connected to a plurality of other nodes by a plurality of links.

76. A method according to claim 75, wherein at least one of said plurality of links connecting said node to said plurality of other nodes is associated with a phoneme and wherein at least one of said links connecting said node to said plurality of other nodes is associated with a word.

- 77. A method according to claim 61 or any claim dependent thereon, wherein said speech recognition system generates data defining a weighting for the phonemes associated with said links.
- 78. A method according to claim 61 or any claim dependent thereon, wherein said speech recognition system generates data defining a weighting for the words associated with said links.
 - 79. A method according to claim 61 or 62 or any claim dependent thereon, further comprising the step of associating said annotation data with said data file.

80. A method according to claim 62 or any claim dependent thereon, wherein said converting step uses an automatic phonetic transcription unit which generates said phoneme data for words within the typed input.

5

81. A method according to claim 63 or any claim dependent thereon, wherein said step of converting words into phonemes uses an automatic phonetic transcription unit which generates said phoneme data for words within the text data output by said character recognition unit.

10

82. A method according to claim 63 or any claim dependent thereon, further comprising the step of associating said annotation data with either said received image data or with said text data.

15

83. A method according to claim 63 or any claim dependent thereon, wherein said receiving step uses a document scanner or a facsimile machine.

20

84. A method of searching a data file including annotation data in response to an input query, the method comprising the steps of:

generating phoneme data and word data corresponding to the input query;

25

searching the data file based on the phoneme data and/or the word data and the annotation data; and

outputting search results in dependence upon the result of said searching step.

- 85. A method according to claim 84, wherein said annotation data defines a phoneme and word lattice comprising:
- 35
- (i) data for defining a plurality of nodes within the lattice and a plurality of links connecting the nodes

WO 00/54168 PCT/GB00/00718

within the lattice;

(ii) data for associating a plurality of phonemes of the phoneme data with a respective plurality of links; and

(iii) data for associating at least one word with at least one of said links.

86. A method for storing a data file into a database, the method comprising the steps of:

combining the data file with annotation data corresponding to the data file, the annotation data including phoneme data; and

storing the data file with the annotation data.

87. An apparatus for searching a data file including annotation data, in response to an input query, the apparatus comprising:

means for generating phoneme data and word data corresponding to the input query;

means for searching a data file based on the phoneme data and/or the word data and the annotation data; and

means for outputting a search result in dependence upon the result of said searching means.

- 88. An apparatus according to claim 87, wherein said annotation data defines a phoneme and word lattice, and comprises:
- (i) data defining a plurality of nodes within the lattice and a plurality of links connecting the nodes within the lattice;
- (ii) data associating a plurality of phonemes of the phoneme data with a respective plurality of links; and
- (iii) data associating at least one word with at least one of said links. $\,$

5

10

15

20

25

5

10

20

30

35

89. An apparatus for storing a data file into a database, the apparatus comprising:

means for inputting the data file and annotation data corresponding to the data file, the annotation data including phoneme data; and

means for storing the data file with the annotation data.

90. A medium for storing a data file, the data file comprising:

an audio data; and

an annotation data corresponding to the audio data, said annotation data including phoneme data.

91. A medium for storing a data file, the data file comprising:

video data;


audio data corresponding to the video data; and annotation data corresponding to the audio data, the annotation data including phoneme data.

92. A medium for storing a data file, the data file comprising:

text data; and

- annotation data corresponding to the text data, said annotation data including phoneme data.
 - 93. Data including audio data and further comprising annotation data corresponding to the audio data, which annotation data includes phoneme data.
 - 94. Data including video data and further comprising audio data corresponding to the video data and annotation data corresponding to the audio data, which annotation data includes phoneme data.

- 95. Data including text data, the data further comprising annotation data corresponding to the text data, which annotation data includes phoneme data.
- 96. A data carrier carrying data according to any of claims 1 to 13 or processor implementable instructions for controlling a processor to implement the method of any one of claims 14 to 23 or 59 to 83 or 84 to 86.
- 97. Processor implementable instructions for controlling a processor to implement the method of any one of claims 14 to 23 or 59 to 83 or 84 to 86.








Fig. 2









Fig. 5







Fig. 6b






Fig. 8





Fig. 9

10/21







Fig. 11






Fig. 13




Fig. 14

15/21




Fig. 15

PASOCS TO THE PROPERTY.




Fig. 16




Fig. 17




Fig. 18

BNSDO013. 4 TO 11 TO 11 S




Fig. 19





Fig. 20

4807: : 50 mm.



.......

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 14 September 2000 (14.09.2000)

PCT

(10) International Publication Number WO 00/54168 A3

(51) International Patent Classification7: G06F 17/30. G10L 15/00

Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YJ (GB).

(21) International Application Number: PCT/GB00/00718

(22) International Filing Date: 1 March 2000 (01.03.2000) (74) Agents: BERESFORD, Keith, Denis, Lewis et al.: Beresford & Co., 2-5 Warwick Court, High Holborn, London WCIR 5DJ (GB).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,

BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,

IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,

RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,

MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,

GA, GN, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

9905201.1	5 March 1999 (05.03.1999)	GB
9905186.4	5 March 1999 (05.03.1999)	GB
9905160.9	5 March 1999 (05.03.1999)	GB
9905199.7	5 March 1999 (05.03.1999)	GB
9905187.2	5 March 1999 (05.03.1999)	GB
	•	

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 30-2 3-chome Shimomaruko, Ohta-Ku, Tokyo (JP).

Published:

With international search report.

UG. US. UZ, VN, YU, ZA, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for only): CHARLESWORTH, Jason, Peter, Andrew [GB/GB]; Canon Research Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YJ (GB). RAJAN, Jebu, Jacob [IE/GB]; Canon Research Centre Europe Limited, 1 Occam Court, Occam Road, Surrey Research Park, Guildford, Surrey GU2 5YJ (GB). GARNER, Philip, Neil [GB/GB]; Canon Research

(88) Date of publication of the international search report: 14 December 2000

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DATABASE ANNOTATION AND RETRIEVAL



(57) Abstract: A data structure is provided for annotating data files within a database. The annotation data comprises a phoneme and word lattice which allows the quick and efficient searching of data files within the database in response to a user's input query. The structure of the annotation data is such that it allows the input query to be made by voice and can be used for annotating various kinds of data files, such as audio data files, video data files, multimedia data files etc. The annotation data may be generated from the data files themselves or may be input by the user either from a voiced input or from a typed input.

INTERNATIONAL SEARCH REPORT

Inten nal Application No PCT/GB 00/00718

A. CLASSII IPC 7	FICATION OF SUBJECT MATTER G06F17/30 G10L15/00		
According to	o International Patent Classification (IPC) or to both national class	sification and IPC	·
B. FIELDS	SEARCHED		
Minimum do IPC 7	ocumentation searched (classification system followed by classification sy	cation symbols)	• 1
Documentat	tion searched other than minimum documentation to the extent th	at such documents are included in the fields s	earched
	lata base consulted during the international search (name of data ternal, WPI Data, PAJ, INSPEC, COM		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	e relevant passages	Relevant to claim No.
X	GAGNOULET C ET AL: "MAIRIEVOX: VOICE-ACTIVATED INFORMATION SYS SPEECH COMMUNICATION,NL,ELSEVIE PUBLISHERS, AMSTERDAM, vol. 10, no. 1, 1 February 1991 (1991-02-01), p	STEM" ER SCIENCE	1
	XP000202912 ISSN: 0167-6393 page 24, left-hand column, line 19 page 24, right-hand column, par - paragraph 2.3; figure 1B	e 14 - line	
		-/	:
		-/	
			i
		·	
X Fur	ther documents are listed in the continuation of box C.	Patent family members are listed	in annex.
A docum	ategones of cited documents : nent defining the general state of the lart which is not idered to be of particular relevance.	T° later document published after the into or priority date and not in conflict with cited to understand the principle or the	the application but
E earlier filing *L* docum which	document but published on or after the international date lent which may throw doubts on priority claim(s) or his cited to establish the publication date of another	"X" document of particular relevance; the cannot be considered novel or canno involve an inventive step when the de "Y" document of particular relevance; the	t be considered to ocument is taken alone
O, qocnu	on or other special reason (as specified) ment referring to an oral disclosure, use, exhibition or r means ment published phor to the international filling date but	cannot be considered to involve an in document is combined with one or m ments, such combination being obvic in the art.	iventive step when the ore other such docu-
later	than the priority date craimed	*&* document member of the same patent	
	e actual completion of the international search 29 August 2000	Date of mailing of the international se	arch report
Name and	t mailing address of the ISA European Patent Office, P.B. 5818 Patendaan 2 NL = 2280 HV Pijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl. Fax: (+31-70) 340-3016	Fournier, C	

INTERNATIONAL SEARCH REPORT

Inter anal Application No
PCT/GB 00/00718

		PCT/GB 00/00718			
	(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT lategory * Citation of document, with indication, where appropriate, of the relevant passages				
Category •	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.			
A	WITBROCK M J ET AL: "Using words and phonetic strings for efficient information retrieval from imperfectly transcribed spoken documents" PROCEEDINGS OF THE 1997 2ND ACM INTERNATIONAL CONFERENCE ON DIGITAL LIBRARIES; PHILADELPHIA, PA, USA, 'Online! 23 - 26 July 1997, pages 30-35, XP002146047 Retrieved from the Internet: <url:http: afs="" ale="" cs="" d197.html="" docs="" idvl="" user="" www.cs.cmu.edu="" x=""> 'retrieved on 2000-08-29!</url:http:>	1			
X	abstract page 3, line 32 -page 4, line 6	14,24, 34,36, 59,61, 84,86, 87,89-97			
Α	S. CASSIDY & J. HARRINGTON: "EMU: an Enhanced Hierarchical Speech Data Management System" PROC. OF 6TH SPEECH SCIENCE AND TECHNOLOGY CONFERENCE, ADELAÏDE, AUSTRALIA, 1996, pages 381-386, XPO02145977	1-8,14, 24, 34-38, 59-62			
X	page 382, line 1 -page 383, line 6; figure 2	84,86, 87,89, 90,93, 96,97			
Α	EP 0 649 144 A (IBM) 19 April 1995 (1995-04-19)	1,3,5-9, 14,24, 34-38, 59-62, 84,86, 87,89-97			
	column 1, line 24 - line 30 column 13, line 37 -column 14, line 8 column 6, line 3 -column 12, line 25				
Α	EP 0 597 798 A (IBM) 18 May 1994 (1994-05-18) -	14, 21-24, 31-38, 59-62, 84,87, 89-97			
	column 2, line 35 - line 41 column 4, line 9 - line 58 				


INTERNATIONAL SEARCH REPORT

information on patent family members

Inter mai Application No PCT/GB 00/00718

Patent document cited in search repor	t í	Publication date	(Patent family member(s)	Publication date
EP 0649144	A	19-04-1995	DE DE JP JP US	69422466 D 69422466 T 2986345 B 7199379 A 5649060 A	10-02-2000 06-07-2000 06-12-1999 04-08-1995 15-07-1997
EP 0597798	Α	18-05-1994	JP JP	2741833 B 6274533 A	22-04-1998 30-09-1994

BURRORS PARTY CONTRACTOR AT THE



XP-002192893

CONNECTIVITY

175

Thus condition (1') is satisfied; condition (2') is obviously satisfied.

Q.E.D.

2. Articulation vertices and blocks

A vertex whose removal from the graph increases the number of connected components is called an *articulation vertex*. An edge whose removal from the graph increases the number of connected components of the graph is called an *isthmus*. Using these definitions, we can redefine 2-connectivity: A graph is 2-connected if, and only if, it is of order $n \ge 3$, connected, and has no articulation vertices.

A set A of vertices in graph G that generates a subgraph G_A that is connected and without articulation vertices and is maximal with respect to this




Fig. 9.2. Cactus

property is called a *block*. Thus, subgraph G_A is either 2-connected (if |A| > 2), or an isthmus of G (if |A| = 2), or an isolated vertex of G (if |A| = 1). It is left to the reader to verify that the graph in Fig. 9.2 has 9 articulation vertices, 6 isthmi, and 13 blocks.

A chord of an elementary cycle is defined to be an edge that joins two non-consecutive vertices of the cycle. A cycle of length 3 has no chords. A cycle of length 4 can have 0, 1 or 2 chords.

A cactus is defined to be a connected graph in which every block is either an isthmus or an elementary cycle without chords (see Fig. 9.2).

The principal characteristics of 2-connected graphs are described in the following theorem.

This Page Blank (uspto)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)